

The PuriCare 500IG is ideal for cleaning polluted air due to its five-micron pre-filter and one-micron medium-effect filter, which complement the function of air filtration systems as dust collectors and workshop vacuum cleaners. For airborne dust and wood pellets,the1/8 motor-driven airflow agitates contaminants that adhere to machines and tools and collect airborne dust. These dirty particles are then filtered by the device with clean and odorless air.

PuriCare 500IG Air filtration System compared to PuriCare 500, its unique double ionization technology produces equal amounts of positive and negative ions. Particles in the air are charged by ions, which cause the particles to aggregate and be captured by the filter. And the trace amounts of ozone produced during operation can neutralize harmful pollutants and odors. Even in a 500 sq. ft.carpenter's shop/DIY house, the device also works great.

Additionally, the PuriCare 500IG can generate an airflow of 500 CFM at its peak, which can absorb almost all harmful air particles. This highly concentrated airflow is an essential air-cleaning device for wood carving, sanding, turning, scroll sawing, and dust mixing.

| Features

cETL Certified	
1/8 Low Noise Motor	
Power-On Indicator Light	
3-Stage Air Filtration System	
Continuous Model	
RF Remote Control	
Three-Speed Control Option	
26 ft. Range RF Remote	
6.5 ft. AC Cord with Cord Management	
Built-In Ion Generator	

Not Affected by Temperature		
Automatic Hour Meter Displays Run Time		
Built-In Timer Shuts Down the Device		
Easy Handling		
Smallest Size		
Working Timer		
Two Fixed Installation Structures		
• Sheet Metal Spray Shell With Strong Corrosion		

IKey Design Features

- Greater air circulation speed than the competition, with three speed options: 350, 450, and 500 CFM.
- Protects the respiratory system, reduces harmful chemicals caused by retained dust and artificial wood chips, and prevents carcinogenic complications.
- Long-lasting 1/8 powerful motor, with a maintenance-free bearing motor.
- · Limited noise and quiet operation.
- RF remove control, regardless of obstructions, up to 26 ft.
- Lightweight and compact linear sheet metal spray-molded housing that is wipeable and chemical resistant, with cleverly designed buckle handles on both sides.
- Dual-ion technology charges air particles with extra electrons, dispersing negative ions for deep cleaning. It also minimizes dust, dander, pollen and other allergens and pollutants.


Control Panel



Two Simple Mounting Approaches

- Method 1: Four eyebolts are suspended from the ceiling.
- Method 2: Screw the machine to the wall with four M4 screws.







Add: 8605 SANTA MONICA BLVD#79525 WEST HOLLYWOOD, California, 90069 USA

| Application

The PuriCare 500IG is designed to improve air quality in medium to large woodworking or metalworking workshops (i.e. saws, sanders, planers). It is specially strengthened in motor and air volume, which can absorb pollutants from machines, pads, tools, walls and windowsills more

Guard Your Health:

Air filtration systems designed for woodworking workshops can purify the air by capturing particles as small as 0.001 mm. Dust collectors cannot capture particles of this size. Thus, without life-threatening wood chips that are too minuscule to be caught by other purification systems. However, not only does the PuriCare 500 IG improve air quality, but also it improves your moods by making the air fresher!

Extract:The PuriCare 500IG's unique double ionization technology makes particles in the air charged by ions, causing them to aggregate and be captured by the filter. At the same time, active oxygen is generated to remove odors, volatile organic compounds (VOC) from tobacco, food, pets, paints, mold and mildew, and even carcinogenic formaldehyde emitted from furniture, laminate floors, and wooden cabinets.

APPLICATION	PuriCare 500 IG
Woodshop	
Metal Workshop	
DIY Room	
Salon	
Portable Job Site	
Basement Pottery	
Studio	
Hay Chopping Station	

|Specifications

Power	115 V / 60 Hz
Current	1.0 A
Size For	Up to 500 sq.ft.
Outer Filter	5 microns
Inner Filter	1 micron
Airflow	350, 450, 500 CFM
Sound Pressure Level	< 61 dBA
Feet	Rubber feet
Cord	6.5 ft
Weight	25.5 lbs
Dimensions (W × H × D) 20.1 × 17 × 11 in
	20":308 Sets
Loading Quantity	40":644 Sets
	40"HQ:736 Sets

Replacement Parts

- Grill exhaust
- Blades & motors
- Pre-filter
- Medium efficiency filter
- RF remote control

E-mail: sales@purisystems.com