



GF600A Air Mover

SPECIFICATIONS

Features

High Airflow	✓
Lightweight Design	✓
High-Performance and Energy-Efficient	✓
Easy Maintenance	✓
3-Speed Settings	✓
Stackable	✓

Technical Specifications

Airflow	600 CFM
Noise Level	≤65 dBA
Weight	7.94 lbs
Dimensions	11.81 × 9.13 × 12.48 in.
Operating Voltage	110 - 120 V
Power Cord Length	10 ft.
Certification	ETL



Color Options: Blue, Yellow, Red

PRODUCT APPLICATION

The **AlorAir GF600A** Air Mover is a professional-grade device that combines efficiency, versatility, and portability. Its three adjustable airflow settings ensure rapid drying of surfaces such as carpets, floors, furniture, windows, and walls.

This Air Mover is not only versatile but also extremely flexible in use. **With 3-speed settings and 5 operating angles** (0°, 90°, +10°, -10°, 45°), it is ideal for air drying as well as effectively improving indoor ventilation and air circulation.

Designed for commercial and industrial environments, the AlorAir GF600A Air Mover is equipped with a 10-foot power cord and timer for easy use. Its durable housing ensures reliability in large-scale drying, cleaning, and restoration projects. The AlorAir GF600A Air Mover can be combined with AlorAir's air purifiers and dehumidifiers to form a complete, comprehensive water damage restoration system.

In addition, the device offers excellent portability. It features a plug-and-play design—just plug it in and start using. Lightweight and compact, it's easy to store and transport, whether you're heading to a job site or moving it from room to room. For contractors, restoration specialists, or anyone who needs a portable solution, this device offers unmatched portability and convenience.

KEY DESIGN FEATURES

- 3-Speed Adjustable Airflow
- Stackable Design
- Built-in Cord Wrap
- 10 ft. Power Cord
- Multi-Angle Airflow (5 Angles)
- 600 CFM Airflow



WIDE COVERAGE & VERSATILE ANGLES



ALORAIR SOLUTIONS INC.

Web: www.alorair.com

E-mail: sales@alorair.com

Address: 14752 Yorba Ct, Chino, CA 91710, US

Tel: (888) 990-7469

